

■ H-Profile 62

- Minimum model size of 62 x 90 mm with simultaneous light up and down at same position
- Light figures possible
- Combination with spotlights
- Combination with ceiling light modules



Light insert, beaming direct/indirect



lamp	article no.	length (mm)	weight (kg)
2x1x54 W	HP62 254-5/DI	L1180	1,20
2x1x49 W	HP62 249-5/DI	L1480	1,40
2x1x80 W	HP62 280-5/DI	L1480	1,40

Light insert, beaming direct



lamp	article no.	length (mm)	weight (kg)
1x54 W	HP62 254-5/D	L1180	1,00
1x49 W	HP62 249-5/D	L1480	1,20
1x80 W	HP62 280-5/D	L1480	1,20

Light insert, beaming only indirect




lamp	article no.	length (mm)	weight (kg)
2x1x54 W	HP62 254-5/I	L1180	1,10
1x49 W	HP62 249-5/I	L1480	1,20
1x80 W	HP62 280-5/I	L1480	1,20



Decorative glass



lamp	article no.	length (mm)	weight (kg)
1x54 W	HP62-DG54	L1300	1,60
1x49/80 W	HP62-DG80	L1600	2,20



Parabolic grid

for light insert	article no.	length (mm)	weight (kg)
1x54 W	HP62-PR54	L1180	1,00
1x80 W	HP62-PR80	L1480	1,20

Light inserts with through wiring 3 x 1.5 mm² (no dimmer)
 Light inserts can be fitted without tools
 Lighting techniques interchangeable
 As a special model the direct and indirect light components can be served by individual electronic control gears

